

## Technical Data Sheet

### Texol Multisyn™ 15W-40 ULTRA

Super high performance heavy duty diesel engine lubricant

#### Product description

Texol Multisyn™ 15W-40 Ultra is a superior performance formulation featuring high quality solvent refined base stock technologies. This advanced lubricant is designed with a superior additive formulation and a high durability viscosity index improver maximising long term wear protection and resistance to bearing corrosion in very demanding operating situations.

Texol Multisyn™ 15W-40 Ultra delivers complete engine protection to high powered turbocharged diesel trucks and buses over extended oil drain periods. Texol Multisyn™ 15W-40 Ultra offers exceptional engine wear protection, eliminating and maximising engine power output.

#### Customer benefits

Texol Multisyn™ 15W-40 Ultra meets and exceeds the very latest ACEA and API performance requirements, and surpasses international original equipment manufacturers performance standards for heavy duty diesel engines. This highly durable lubricant offers outstanding engine cleanliness, through high efficiency detergency and dispersancy Technologies and is highly resistant to oil thickening in the high temperature environments of latest generation close tolerance turbocharged and naturally aspirated diesel power units.

Featuring exceptional low foam performance, Texol Multisyn™ 15W-40 Ultra offers highly reliable and extremely durable component protection and engine performance over significantly extended oil drain intervals.

#### Applications

- Recommended for use in naturally aspirated and turbocharged heavy duty diesel truck and bus engines operating under a variety of conditions, where extended drain periods are required.

## Technical Data Sheet

### Texol Multisyn™ 15W-40 ULTRA

Super high performance heavy duty diesel engine lubricant

### Typical Properties

Property (Unit)	15W-40 ULTRA	Method
Density at +15 °C	888	ASTM D4052
Viscosity @40°C, cSt	107.6	ASTM D445
Viscosity @100°C, cSt	14.2	ASTM D445
Viscosity Index	136	ASTM D2270
Flash Point, °C	220	ASTM D92
Pour Point, °C	-38	ASTM D97
Sulphated Ash, %wt	1.29	ASTM D874
Total Base Number, mg KOH/g	10.5	ASTM D2896

### Specifications

Multisyn™ 15W-40 Ultra meets:

- Certified against: ACEA E7-04  
ACEA A2-96 / A3-02 / B3-98 / B4-02
- Licensed as: API SL/CI-4
- Allison transmission C-4
- Caterpillar CAT ECF-1
- Cummins CES 20076 / 20077 / 20078
- Mack EO-M Plus
- Mercedes-Benz 228.3 / 229.1
- MTU Type 2
- Renault Truck RLD-2
- Volvo Truck VDS-3

### Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.