

Technical Data Sheet

Texol Multisyn™ DPF 5W-30

Ultra high performance synthetic engine lubricant

Product description

Texol Multisyn™ DPF 5W-30 is a ultra high performance synthetic engine lubricant specially formulated with an advanced technology additive system designed to meet demanding OEM specifications.

Texol Multisyn™ DPF 5W-30 is suitable for both gasoline and diesel passenger cars as well as light duty commercial diesel vehicles. This advanced low SAPS technology lubricant is compatible with diesel particulate filter (DPF) and three way catalytic converter (TWC) systems.

Customer benefits

- Advanced additive technology aids emissions system protection and performance
- Through low SAPS technology designed to protect catalysts and diesel particulate filter systems
- Low temperature fluidity helps ensure rapid oil circulation at cold engine start-up
- Offers protection against deposits and sludge build-up, helping maintain fuel economy
- Advanced synthetic formulation offers long-life, low volatility performance

Applications

- Texol Multisyn™ DPF 5W-30 is suitable for a wide range of gasoline and diesel passenger car or light diesel vans, with or without turbochargers. It is especially designed for extended drain intervals in Europe with DPFs
- Texol Multisyn™ DPF 5W-30 is recommended for vehicles requiring a VW 504.00, VW 507.00 engine oil, also known as VW Longlife III oils, and is backwards compatible with other active and obsolete VW/Audi engine oil specifications

Texol Multisyn™ DPF 5W-30 is unsuitable for some engines. Consult owner's manual or handbook if in doubt.

Technical Data Sheet

Texol Multisyn™ DPF 5W-30

Ultra high performance synthetic engine lubricant

Typical Properties

Property (Unit)	DPF 5W-30	Method
Density at +15 °C	852	ASTM D4052
Viscosity @40°C, cSt	70.2	ASTM D445
Viscosity @100°C, cSt	12.3	ASTM D445
Viscosity Index	170	ASTM D2270
Flash Point, °C	236	ASTM D92
Pour Point, °C	-36	ASTM D97

Specifications

Multisyn™ DPF 5W-30 meets:

- ACEA C3
C3-10
C2 (except for fuel economy)
- BMW BMW LL-04
- Daimler MB- 229.31/229.51
MB- 228.50/228.51
- Volkswagen VW 504.00/507.00 (Longlife III oil)
- Suitable for use in VW 502.00/505.01 engines
- Suitable for use in VW 503.00 and VW 503.01 engines
- Suitable for use in API SN applications

Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.