

## Technical Data Sheet

### Texol Multisyn™ 5W-40

Ultra High performance synthetic multigrade engine lubricant

#### Product description

Texol Multisyn™ 5W-40 is an ultra high performance shear stable synthetic multigrade engine lubricant, designed for use in modern passenger cars.

Texol Multisyn™ 5W-40 is formulated with synthetic base oils combined with high performance additive technology to offer long life engine performance, wear resistance, cold temperature protection and reduce emissions output.

#### Customer benefits

- Stable viscosity control contributes to durable engine protection in arduous high temperature driving, and in colder climates
- Thermal stability aids keep-clean engine performance, helping protect against varnish, sludge and harmful deposit formation
- High performance low temperature fluidity offers reliable engine protection in low temperature conditions
- Promotes lower exhaust emissions performance
- Helps provide greater long-term engine protection, reliability and lower maintenance costs

#### Applications

- Texol Multisyn™ 5W-40 is intended for use in high performance gasoline engines and car & light van diesel engines. It can be used for extended drain intervals where specified by the engine manufacturer
- Texol Multisyn™ 5W-40 is designed for engines that require ACEA A3/B3, ACEA A3/B4, API CF, API SM and the older API gasoline specifications such as API SL, API, SJ, API SH and API SG.
- Texol Multisyn™ 5W-40 has been developed for use in a wide variety of modern gasoline and diesel cars and vans such as BMW, Mercedes Benz, Opel, Renault, Volkswagen, Peugeot, Citroën and others

#### Specifications

Certified against:	ACEA A3/B4 ( includes A3/B3 )
Licensed as:	API SM/CF
Daimler	MB 229.3
GM	GM-LL-B-025
Volkswagen	VW 502.00/505.00

# TEXOL

## Chemical

### Technical Data Sheet

#### Texol Multisyn™ 5W-40

Ultra High performance synthetic multigrade engine lubricant

#### Typical Properties

Property (Unit)	5W-40	Method
Density at +15 °C	858	ASTM D4052
Viscosity @40°C, cSt	82.6	ASTM D445
Viscosity @100°C, cSt	13.8	ASTM D445
Viscosity Index	170	ASTM D2270
Flash Point, °C	224	ASTM D92
Pour Point, °C	-36	ASTM D97

#### Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.